

NOVITANE® CONVEYOR BELT

INDUSTRIAL GRADE - HD Series

Description	Tension Rating	OAG	Lbs. PIW Lineal Foot	Minimum Pulley Diameter	Maximum Width	Color
IG-150/65-COS (16)	150	1/4"	0.133	6"	118"	Clear
IG-150/75-COS (16)	150	1/4"	0.133	6"	118"	Black
IG-150/85-COS (16)	150	1/4"	0.133	6"	118"	Red
IG-150/85-CBS (20)	150	5/16"	0.159	6"	48"	Red
IG-150/95-COS (16)	150	1/4"	0.133	6"	118"	Clear
IG-150/100-COS (14)	150	7/32"	0.130	6"	118"	Clear
IG-200/65-COS (24)	200	3/8"	0.186	10"	79"	Clear
IG-200/65-COS (28)	200	7/16"	0.200	12"	79"	Clear
IG-200/75-COS (24)	200	3/8"	0.186	10"	79"	Black
IG-200/75-COS (28)	200	7/16"	0.200	12"	79"	Black
IG-200/85-GFS (10)	200	5/32"	0.075	5"	72"	Green
IG-200/85-COS (20)	200	5/16"	0.159	8"	79"	Red
IG-200/85-COS (24)	200	3/8"	0.186	12"	79"	Red
IG-200/85-CBS (24)	200	3/8"	0.186	12"	48"	Red
IG-200/85-CBS (32)	200	1/2"	0.213	18"	48"	Red
IG-200/95-COS (16)	200	1/4"	0.123	6"	79"	Clear
IG-200/95-COS (18)	200	9/32"	0.129	8"	79"	Clear
IG-200/95-CBS (24)	200	3/8"	0.186	18"	48"	Clear

